

## 15mm\* DIAMETER STAINLESS STEEL CLAD EARTH RODS

Catalogue No.	Description	Size	Weight (kg)
<b>SDR1512</b>	SDR- 15 - 1200	ø15mm x 1200mm long	1.5
<b>SDR1515</b>	SDR – 15 - 1500	ø15mm x 1500mm long	2.5
<b>SDR1518</b>	SDR – 15 - 1800	ø15mm x 1800mm long	2.7
<b>SDR1520</b>	SDR – 15 - 2000	ø15mm x 2000mm long	3.0
<b>SDR1524</b>	SDR – 15 - 2400	ø15mm x 2400mm long	3.2
<b>SDR1530</b>	SDR - 15 - 3000	ø15mm x 3000mm long	3.5

Stainless Steel Clad Earth Rods are manufactured using Steel to AS3679 and 316 Grade Stainless Steel Tube. Diameter is 15mm nominal\*. All Earth Rods are extendible using couplers and are pre-pointed. Test Reports available by request. Special Lengths made to order.

### ACCESSORIES FOR 15mm DIAMETER STAINLESS STEEL CLAD EARTH RODS

Catalogue No.	Description	Weight (kg)
<b>SC15</b>	Stainless Steel Coupler to extend 15mm Diameter Earth Rod	0.07
<b>DHT15</b>	Driving Head Tool	0.3
<b>TP15</b>	Tapered Point (if required) - Rods are pre-pointed	0.03
<b>TPS15</b>	Star Point for hard driving areas	0.07
<b>ERDP1</b>	Earth Rod Driving Pin	0.01
<b>K900DM</b>	Kango Driving Moil 900 Series	0.72
<b>REB15</b>	REB151050 Clamp Cable Range	0.1
<b>REC35-120</b>	REC35-120 Clamp Cable Range: 35 -120 Invert suit 16mm <sup>2</sup>	0.15
<b>REF15</b>	REF15 Clamp braid/busbar parallel or right angles to Earth Rod	0.20
<b>REP16/50</b>	REP16-50/15 Clamp Cable range: 16-50mm <sup>2</sup>	0.125
<b>REX</b>	REX16-120 Clamp Cable range: 16-120mm <sup>2</sup>	0.26
<b>GE</b>	"Good Earth" Earthing Compound 15kg Bag - covers 0.03mm <sup>3</sup>	15
<b>CEB1</b>	Small Earth Rod Pit with Lid (Concrete)	11
<b>CEB2</b>	Large Earth Rod Pit with Lid (Concrete)	24
<b>MEB1</b>	Metal Earth Rod Pit with hinged Lid	0.08
<b>PEB1A</b>	Small Concrete Earth Rod Pit with hinged lid	7.5
<b>PT205</b>	Small Poly Earth Rod Pit with lockable lid, Max Load: 5000kg	1.8