

19mm DIAMETER COPPER CLAD EARTH RODS

Catalogue No.	Description	Size	Weight (kg)
CR1918	CDR-19-1800	ø19mm x 1800mm long	4.5
CR1924	CDR-19-2400	ø19mm x 2400mm long	5.5
CR1930	CDR-19-3000	ø19mm x 3000mm long	8

Copper Clad Earth rods are manufactured using Steel to AS3679 and H.D. Copper Tube manufactured to AS1572, with a diameter of 19mm nominal*. All Earth Rods are extendible, by using couplers and are pre-pointed. Test Reports are available by request. Special Lengths made to order. Come complete with Fixed Driving Head when not extending as CR1918FDH.

ACCESSORIES FOR 19mm DIAMETER COPPER CLAD EARTH RODS

REX



ET19



Catalogue No.	Description	Weight (kg)
BC19	Brass Coupler to extend 19mm Diameter Earth Rod	0.015
DHT19	Driving Head Tool	0.3
ET19	Airport Earthing Terminal for 19mm Earth Rod	0.75
EC2	Earth Clamp (Cable Range: 16-25mm ²)	0.475
REP16-120	REP16-120 Clamp (Cable Range: 16-120mm ²)	0.205
REP16-120/2	REP16-120/2 Clamp (Cable Range: 16-120mm ²) 2 Parallel Cables	0.4
REX	REX16-120 Clamp (Cable Range: 16-120mm ²)	0.285
RET	RET25-120/3 Clamp (Cable Range: 25-120mm ²) 3 Parallel Cables	0.7
GE	"Good Earth" Earthing Compound 15kg Bag – covers 0.03mm ³	15
CEB2	Large Earth Rod Pit with Lid (Concrete)	24
PEB1/1A	Small Concrete Earth Rod Pit with hinged lid	7.5
PT205L	Small Poly Earth Rod Pit with lockable lid, Max Load: 5000kg	1.8
P20	Polymer concrete c/w steel lid	

Please refer to "Earth Clamps" on page 8-16/17 and "Earth Pits" on page 8-25 for detailed information on these products.