

COMPRESSION EARTH CLAMPS



Made from high conductivity copper. Used where copper earth wire is looped so as not to cut the earth wire, ensuring continuity of the earthing system. Suits vast range of conductors and earth rods (12, 14 and 15mm diameter).

—6 PROFILE EARTHING CONNECTOR – FOR CABLE TO CABLE OR ROD TO CABLE CONNECTION



Catalogue No.	Rod Diameter	Tap	Die Size
	mm	mm <sup>2</sup>	6' Profile
CO/16	12,14 AND 15	16mm <sup>2</sup>	U-997
CO/25	12,14 AND 15	25mm <sup>2</sup>	
CO/35	12,14 AND 15	35mm <sup>2</sup>	or
CO/50	12,14 AND 15	50mm <sup>2</sup>	
CO/70	12,14 AND 15	70mm <sup>2</sup>	DU1315
CO/95	12,14 AND 15	95mm <sup>2</sup>	
CO/120	12,14 AND 15	120mm <sup>2</sup>	

INTERLINK COMPRESSION EARTH CLAMPS.



CO120/CRM

Used where earth wires cross and are interconnected to improve the earthing grid. Solid copper loop is bent at right angles for connection. Copper grit paste is smeared inside earth wire and earth loop holes ensuring a good connection. Consult factory for details.  
To suit 10-15mm rod and 50mm<sup>2</sup> to 120mm<sup>2</sup> wire

“C” PROFILE EARTHING CONNECTOR – FOR ROD TO CABLE CONNECTION

Catalogue No.	Rod Diameter	RUN	DIE SIZE
	mm	mm <sup>2</sup>	‘C’ Profile
C70/95	12,14 and 15mm	50,70 and 95mm <sup>2</sup>	U-997/DU1315

“C” PROFILE EARTHING CONNECTOR – FOR CABLE TO CABLE CONNECTION

Catalogue No.	CABLE RUN	CABLE TAP	DIE SIZE ‘C’ PROFILE
C70/95	95mm <sup>2</sup>	70mm <sup>2</sup>	U-997 OR DU-1315
	95mm <sup>2</sup>	95mm <sup>2</sup>	
	70mm <sup>2</sup>	70mm <sup>2</sup>	



“E” PROFILE EARTHING CONNE+CTOR – FOR CABLE TO CABLE CONNECTION

Catalogue No.	CABLE RUN	CABLE TAP	DIE SIZE “E” PROFILE
E50/70	50mm <sup>2</sup>	50mm <sup>2</sup>	U-O
	70mm <sup>2</sup>	50mm <sup>2</sup>	
	70mm <sup>2</sup>	70mm <sup>2</sup>	
E120/120	95mm <sup>2</sup>	120mm <sup>2</sup>	U997
	95mm <sup>2</sup>	95mm <sup>2</sup>	
	120mm <sup>2</sup>	120mm <sup>2</sup>	

